

Polycril GW FR

Front print, blackout (black back) for displays and roll up banners.



BILD PART NUMBER: BPMEPGW63x164

DESCRIPTION: Endutex Polycril GW FR 63" x 164'

MATERIAL: Resin Coated Polyester Woven Fabric

COMPOSITION: 55% Resin Coated Polyester Woven Fabric
45% polyester

WIDTH:	cm	160	320
	Inches	62	125

Technical Specs Sheet

Characteristic	Specification	Method
Thickness (mm)	0.32	
Total Mass (g/m ²)	320 ± 30	EN ISO 2286-2
Fabric Mass (g/m ²)	145 ± 10	EN ISO 2286-2
Breaking Load (daN/50mm)	L.: 150 T.: 85	EN ISO 1421
Breaking Extension (%)	L.: 25 T.: 25	EN ISO 1421
Tear Strength (daN)	L.: 20 T.: 10	DIN 53363
Burning Behavior	B1	DIN 4102

L-Along T-Across

This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice so please contact our technical service for any additional information you may require. Inches rounded down to the nearest whole number. Updated: 2016/03/02

a product of **ENDUTEX**